



VOLUME trading



*silkwood*

OAK AB



## OAK AB

### DIMENSIONS

		TOLERANCES	
		+	-
Lenght	Up to 5000mm	10 mm	0mm
Width	Up to 1200mm	5 mm	0 mm
Thickness	18, 30, 40mm	1 mm	1 mm
Width of lamellas	40,0 mm	4,0 mm	4,0 mm
Lenght of lamellas	350 mm	200 mm	200 mm

Moisture content: 8% +/- 2%

### FINISHING

Sanding Edge shaping Oiling	SILKWOOD surface finish Sharp, „broken”, beveled, postformed WOCA FDA approved oil
-----------------------------------	--

### QUALITY

	A side	Front and back ends lamella	B side
Sound tight knots max diameter 5 mm	+	-	+
Sound tight knots chipped,	-	-	+
Black knots tight	+	-	+
Natural colour differences	+	+	+
Inbark	-	-	+
Holes, dents	-	-	+
Splits, cracks and other defects from drying	-	-	+
Chipped corners,	-	-	+
Discolouration (metal)	-	-	+
Rot, wormholes	-	-	-
Heart	-	-	+
Heart rays	-	-	+
Sapwood	-	-	+
Fungus	-	-	-
Visual glue lines	0,2 mm	0,2 mm	+
Repairs	-	-	+
Knot repairs	+	+	+